


**Mungo®-Dübel MN**

aus Polyamid (Nylon)

**Tampons Mungo® MN**

en polyamide (nylon)



Grösse grandeur	Bohrloch ø mm ø de forage en mm	Dübellänge mm long. du tampon mm	Schrauben ø mm ø de vis en mm	VE emb.		
					100	1000
4	4	20	2,2 - 3	100	6.80	3.70
5	5	25	2,6 - 4 / M3	100	7.—	4.15
6	6	30	3,5 - 5 / M4	100	7.90	6.40
6 L	6	50	3,5 - 5 / M4	100	11.10	8.90
7	7	25	4,5 - 5 / M4	100	10.30	8.10
8	8	40	4,5 - 6 / M5	100	11.40	9.10
8 L	8	60	4,5 - 6 / M5	50	16.60	13.30
10	10	50	6 - 8 / M6	50	23.20	18.50
12	12	60	8 - 10 / M8	25	34.40	27.50
14	14	70	10 - 12 / M10	20	62.50	49.80
15	15	75	10 - 12 / M10	10	62.50	49.80
16	16	80	12 - 14 / M12	10	105.—	84.—
20	20	90	14 - 16 / M14	5	191.—	153.—

**Mungo®-Lochsteindübel ML**für Montagen auf Backsteinen, Gasbeton, Gips  
usw. Neu mit 4-facher Verdrehsicherungaus Polyamid (Nylon)  
**temperaturbeständig  
von -40°C bis +80°C****Cheville pour corps creux  
Mungo® ML**pour fixations dans briques rouges, béton  
cellulaire, plâtre, etc. Nouveau - 4 dispositifs  
anti-rotationen polyamide (nylon)  
**résistant à la température  
de -40°C jusqu'à +80°C**

Typ type	Bohrloch-ø mm ø de forage en mm	Dübellänge mm longueur du tampons	Schrauben ø mm de vis en mm		
				100	1000
6 x 60	6	60	3,5 - 5,0 M4	28.20	22.80
8 x 80	8	80	5 - 6 M5	45.60	36.—
10 x 90	10	90	7 M6	54.—	43.20
10 x 120	10	120	7 M7	61.50	49.20
14 x 90	14	90	10 M 10	86.50	68.50
14 x 120	14	120	10 M 10	105.—	84.50
				100	
				50	