

Sicherungsmuttern 1 d SNEP-elastic Typ ESN


selbstklemmend

Ecrous de sécurité 1 d SNEP-élastique type ESN

à autofreinage

aus rostbeständigem Stahl A 2

en acier inoxydable A 2

Zugfestigkeit 550–700 N/mm²Résistance à la traction 550–700 N/mm²

d	s	m	100	1000
M 4	7	4	226.70	189.60
M 5	8	5	257.60	212.60
M 6	10	6	284.70	235.80
M 8	13	8	386.40	339.30
M 10	17	10	677.50	594.90
M 12	19	12	935.10	823.90
M 16	24	16	1'766.—	1'560.—
			100	
			50	

Sicherungsmuttern Typ 3-Punkt


Ganzmetall, klemmend

Ecrous de sécurité type 3-points

entièrement métal, serrants

aus rostbeständigem Stahl A 2

en acier inoxydable A 2



d 1	e min.	m max.	s	100	500	1000
M 4	7,66	3,2	7	54.10	48.70	40.80
M 5	8,79	4	8	55.60	50.—	42.30
M 6	11,05	5	10	73.30	65.90	55.90
M 8	14,38	6,5	13	116.—	104.40	87.—
M 10	18,90	8	17	215.10	194.30	169.10
M 12	21,10	10	19	282.10	254.—	219.80
M 16	26,75	13	24	533.30	479.90	417.50
				100		
				50		