


**Gewindefurchende
Senkkopfschrauben**mit metrischem Gewinde
und TX-Antrieb

aus rostfreiem Stahl A2

**Vis formantes le filetage à
tête fraisée**filetage métrique
et six lobes internes (TX)

en acier inoxydable A2




d1	M 2,5		M 3		M 4		M 5		M 6	
d2	4,7		5,5		8,4		9,3		11,3	
k	1,5		1,65		2,7		2,7		3,3	
A	TX 8		TX 10		TX 20		TX 25		TX 30	
L	100	1000	100	1000	100	1000	100	1000	100	1000
5	9.90	7.20								
6	10.20	7.30	11.60	8.50						
8	10.50	7.60	11.80	8.70	15.50	11.40				
10	10.80	7.80	12.10	8.90	17.—	12.30	22.50	16.30		
12	11.90	8.80	12.20	8.90	17.50	13.—	24.70	17.80		
16					21.10	15.60	30.20	21.10	41.—	32.80
20					24.30	17.40	35.90	25.80	45.50	36.40
25							38.20	28.20	47.50	38.10
30							40.90	31.50	51.30	41.10
	100		100		100		100		100	

**Gewindefurchende
Linsenschrauben**mit metrischem Gewinde,
Kopf nach DIN 7985
und TX-Antrieb

aus rostfreiem Stahl A2

**Vis formantes le filetage à
tête cylindrique bombée**avec filetage métrique;
selon DIN 7985
et à six lobes internes (TX)

en acier inoxydable A2



d 1	M 2,5		M 3		M 4		M 5		M 6	
d 2	5		6		8		10		12	
k	2,1		2,5		3,2		3,9		4,7	
A	TX 8		TX 10		TX 20		TX 25		TX 30	
L	100	1000	100	1000	100	1000	100	1000	100	1000
4	10.80	8.10								
5	10.90	8.20	11.40	8.75						
6	11.60	8.90	11.50	8.80	19.80	15.50				
8	11.70	8.95	11.60	8.90	19.90	15.60	27.90	21.40		
10	11.80	9.10	15.50	11.90	20.30	15.80	29.90	22.90	46.80	36.10
12	11.90	9.20	16.30	12.60	22.50	17.50	31.50	24.50	46.90	36.10
16			17.50	13.50	25.60	19.70	38.20	29.20	49.90	38.50
20			20.30	15.70	29.20	22.50	46.80	36.10	57.50	44.20
25					35.50	27.50	53.80	41.50	65.50	50.40
	100		100		100		100		100	