


Einbruchssichere Schrauben
mit Innensechskant
und Zapfen, Pin-Heragon

aus rostbeständigem Stahl A 2



Vis à l'épreuve de
l'effraction à six pans
creux et têtou, Pin-Heragon

en acier inoxydable A 2

ähnl. ISO 7380

approx. ISO 7380

d	M 3		M 4		M 5		M 6		M 8	
D	5,7		7,6		9,5		10,5		14	
k	1,7		1,65		2,2		3,3		4,4	
s	2		2,5		3		4		5	
L	100	500	100	500	100	500	100	500	100	500
6			63.—	54.80						
8	55.—	46.70	67.80	58.70						
10	59.50	51.90	75.60	66.10	84.60	73.40	99.20	86.60	155.90	135.20
12	65.20	56.50	81.60	70.50	88.90	77.10	99.20	86.60	155.90	135.20
16			83.—	71.80	90.40	78.60	100.60	87.20	163.60	142.10
20			90.40	78.60	96.40	83.80	116.—	100.30	177.80	154.80
25			93.40	80.80	108.30	94.20	119.90	104.20	193.20	167.90
30			101.80	88.60	118.50	103.—	130.10	113.10	217.70	217.70
40					131.—	113.80	136.50	92.—	216.—	154.—
50							153.—	105.—	234.—	165.—
60										
	52.50	44.60								
	100		100		100		100		100	


Sicherheitsschrauben – A2
SECUFAST® – Vis Inviolables

Blechschruben – Snake Eyes® Spanners
Vis tôle TC-2 trous




Panhead
INOX A2

Blechschruben – Snake Eyes® Spanners
Vis tôle TC-2 trous




Flathead
INOX A2

Metrische Schrauben – Snake Eyes® Spanners
Vis métaux TC-2 trous



Panhead
INOX A2

Metrische Schrauben – Snake Eyes® Spanners
Vis métaux TC-2 trous



Flathead
INOX A2

Metrische Schrauben (DIN 7991) – SecuFast®
Vis métaux TFHC + Téton



Flathead
INOX A2