

Einsatzbüchsen RAMPA®
Typ ES


mit Innen- und Aussengewinde,
selbstschneidend

aus Messing

Douilles noyées RAMPA®
type ES

avec filetage intérieur et extérieur, auto-
taraudantes

en laiton




Nenngrösse dimension nom.	d 1 mm	d 2 mm	L mm	Bohrlochtiefe mm prof. du trou à percer mm	100	1000
M 3/5 x 6	M 3	M 5 x 0,5	6	8	46.20	39.60
M 4/6,5 x 8	M 4	M 6,5 x 0,75	8	10	36.—	30.—
M 5/8 x 10	M 5	M 8 x 1	10	13	44.40	37.80
M 6/9 x 12	M 6	M 9 x 1	12	15	52.80	45.—
M 8/12 x 15	M 8	M 12 x 1,5	15	18	90.—	76.50
M 10/14 x 18	M 10	M 14 x 1,5	18	22	139.—	118.—
M 12/16 x 22	M 12	M 16 x 1,5	22	26	216.—	186.—
					100	

Quergewindebolzen
RAMPA® Typ 2Q

aus Stahl
verzinkt-blau

Goujaon avec filetage
transversal RAMPA® type
2Q

en acier
zingué-bleu



D	L	D	C	100	500
10	48	M 6	32	145.—	123.—
10	60	M 6	40	185.—	155.—
10	82	M 6	64	225.—	190.—
12	70	M 8	52	270.—	225.—
				10	
				1	

Bestellbeispiel 10 x 48 / M 6 / Exemple de commande 10 x 48 / M 6