


**Zylinderschrauben
mit Innensechsrund**
**Vis à tête cylindrique
à six lobes internes**

aus Stahl, Qual. 8.8
verzinkt-blau

en acier, qual. 8.8
zingué-bleu

approx. ISO 14580



ähnl. ISO 14580

	M 3			M 4			M 5			M 6		
d 1	5,5			7			8,5			10		
d 2	2,4			2,8			3,5			4		
k max.	1,8			2,1			2,4			3		
h	10			20			25			30		
l-6 Nr./no.	1,27			1,3			1,5			1,8		
t max.	2,8			3,95			4,5			5,6		
m												
L	100	500	1000	100	500	1000	100	500	1000	100	500	1000
6	13.90	12.50	10.40									
8	14.10	12.70	10.70	12.80	11.90	9.60	14.40	13.10	10.80	18.—	16.50	13.50
10	14.50	13.—	10.80	13.20	12.10	10.10	13.90	12.70	10.50	20.40	18.80	15.50
12	17.—	15.20	12.50	13.90	12.70	10.50	14.90	13.70	11.20	21.90	20.20	16.50
16	18.20	16.40	13.50	15.30	14.—	11.50	15.40	14.10	11.60	26.70	24.60	20.20
20	20.20	18.20	14.90	16.—	14.80	12.—	18.60	17.10	13.90	29.50	27.20	22.10
25							20.70	19.10	15.70	30.10	27.70	22.60
30										30.50	28.—	23.60
	100			100			100			100		

	M 8		
d 1	13		
d 2	5		
k max.	3,75		
h	40		
l-6 Nr./no.	2,2		
t max.	6,75		
m			
L	100	500	1000
10	32.40	29.80	24.90
12	35.70	32.80	27.50
16	34.40	31.60	27.60
20	37.40	34.40	28.60
25	42.10	38.70	32.—
30	48.40	44.50	37.40
40	57.—	52.10	43.70
	100		