


## Ringschrauben

aus Stahl C 15 E  
**verzinkt-blau**

## Vis à anneau

en acier C 15 E  
**zingué-bleu**

~ISO 3266



d 1	l	d 3	d 4	h	100	500
(M 6) *	12	27	14	27,5	276.—	248.—
M 8	13	36	20	36	276.—	250.—
M 10	17	45	25	45	348.—	313.—
M 12	20,5	54	30	53	432.—	389.—
(M 14) *	27	63	35	62	624.—	561.—
M 16	27	63	35	62	647.—	583.—
(M 18) *	30	72	40	71	900.—	793.—
M 20	30	72	40	71	912.—	821.—
(M 22) *	36	90	50	90	1'439.—	1'295.—
M 24	36	90	50	90	1'380.—	1'242.—
(M 27) *	45	108	60	109	3'058.—	2'752.—
M 30	45	108	60	109	2'650.—	2'385.—
(M 33) *	54	126	70	128	5'216.—	
M 36	54	126	70	128	4'377.—	4'175.—
M 42	63	144	80	147	8'152.—	6'155.—
M 48	68	166	90	168	13'307.—	
					1	

\* in DIN 580 nicht enthalten / \* ne sont pas dans DIN 580


## 547210100

## DIN 582 C 15 E

## Ringmuttern

aus Stahl C 15 E  
**blank**

## Ecrous à anneau

en acier C 15 E  
**clairs**

d 1	d 2	d 3	d 4	h	k	100	500
M 8	20	36	20	36	8	234.—	210.—
M 10	25	45	25	45	10	318.—	286.—
M 12	30	54	30	53	12	390.—	351.—
(M 14) *	35	63	35	62	14	516.—	464.—
M 16	35	63	35	62	14	540.—	486.—
(M 18) *	40	72	40	71	16	816.—	734.—
M 20	40	72	40	71	16	755.—	680.—
(M 22) *	45	81	45	80	18	1'559.—	1'403.—
M 24	50	90	50	90	20	1'343.—	1'209.—
(M 27) *	50	90	50	90	20	2'578.—	
M 30	65	108	60	109	24	2'650.—	
M 36	75	126	70	128	28	5'336.—	
(M 39) *	75	126	70	128	28	7'553.—	
M 42	85	144	80	147	32	8'009.—	
						1	

\* in DIN 582 nicht enthalten / \* ne sont pas dans DIN 582