


Unterlagsscheiben ohne Fase

Rondelles sans chanfrein

VSM 13904

aus Stahl gestanz, 140 HV
verzinkt-blau

en acier étampé, 140 HV
zingué-bleu



für Schrauben pour vis	d 1	d 2	s	100	500	1000	10000
M 2	2,2	5	0,3	3.95	3.15	2.10	0.95
M 2,5	2,7	6	0,5	3.95	3.15	1.60	0.75
M 3	3,2	7	0,5	3.95	3.15	1.60	0.75
(M 3,5)	3,7	8	0,5	3.95	3.15	1.60	0.75
M 4	4,3	9	0,8	3.95	3.15	1.60	0.80
(M 4,5)	4,8	12	1	4.05	3.25	2.10	1.90
M 5	5,3	10	1	3.95	3.15	1.80	0.80
M 6	6,4	12	1,6	3.95	3.15	1.80	1.10
(M 7)	7,4	14	1,6	4.05	3.25	1.85	1.45
M 8	8,4	16	1,6	4.05	3.25	2.10	1.70
M 10	10,5	20	2	7.20	5.40	3.50	3.—
M 12	13	24	2,5	7.50	5.90	5.40	4.85
M 14	15	28	2,5	9.50	8.50	7.40	6.90
M 16	17	30	3	11.40	10.—	8.90	8.20
(M 18)	19	34	3	18.20	16.20	13.80	13.—
M 20	21	37	3	19.80	17.80	14.90	13.70
(M 22)	23	39	3	24.70	22.20	19.50	18.20
M 24	25	44	4	32.10	28.90	24.90	23.30
(M 27)	28	50	4	56.—	50.20	45.—	41.40
M 30	31	56	4	59.—	52.90	47.70	43.80
M 33	34	60	5	102.—	81.50		
M 36	37	66	5	132.—	105.50		
				100			
				50			

Toleranzen nach DIN 522 A/ISO4759 / Tolérances selon DIN 522 A/ISO4759