


Unterlagsscheiben ohne Fase

Rondelles sans chanfrein

VSM 13904

aus Stahl gestanzt, 140 HV
feuerverzinkt

en acier estampé, 140 HV
zingué au feu



für Schrauben pour vis	d 1	d 2	s	100	500	1000
M 6	6,4	12	1,6	7.70	6.70	4.35
M 8	8,4	16	1,6	7.80	6.90	4.95
M 10	10,5	20	2,0	10.30	9.10	8.—
M 12	13	24	2,5	14.30	12.70	11.40
(M 14)	15	28	2,5	24.60	22.—	19.10
M 16	17	30	3	27.—	24.—	21.50
(M 18)	19	34	3	40.80	36.30	32.50
M 20	21	37	3	42.10	37.40	34.—
(M 22)	23	39	3	54.—	48.10	43.10
M 24	25	44	4	82.50	73.—	66.—
(M 27)	28	50	4	118.—	105.—	94.—
M 30	31	56	4	132.—	118.—	105.50
(M 33)	34	60	5	168.—	149.—	134.—
M 36	37	66	5	210.—	187.—	167.—
(M 39)	40	72	6	234.—	208.—	186.—
				100		
				50		
				1		

Toleranzen nach DIN 522 A/ISO 4759 / Tolérances selon DIN 522 A/ISO 4759


Unterlagsscheiben ohne Fase

Rondelles sans chanfrein

VSM 13904

aus Stahl gestanzt, 140 HV
verzinkt-schwarz

en acier estampé, 140 HV
zingué-noir



für Schrauben pour vis	d 1	d 2	s	100	500	1000
M 3	3,2	7	0,5	3.65	3.05	1.85
M 4	4,3	9	0,8	3.65	3.05	1.85
M 5	5,3	10	1	3.65	3.05	1.85
M 6	6,4	12	1,6	3.65	3.05	1.85
M 8	8,4	16	1,6	4.25	3.35	2.30
M 10	10,5	20	2	7.80	6.30	4.65
M 12	13	24	2,5	9.—	7.10	7.10
(M 14)	15	28	2,5	17.40	15.70	13.70
M 16	17	30	3	15.70	14.20	12.90
M 20	21	37	3	25.80	23.50	20.20
M 24	25	44	4	46.20	42.—	36.80
				100		
				50		

Toleranzen nach DIN 522 A/ISO 4759 / Tolérances selon DIN 522 A/ISO 4759