



Unterlagsscheiben ohne Fase

Rondelles sans chanfrein

aus Stahl gestanz,
verzinkt-blau

en acier étampé,
zingué-bleu




für Schrauben pour vis	d 1	d 2	s	100	500	1000
M 2,5	2,7	8	0,8	3.85	2.55	1.10
M 3	3,2	9	0,8	3.85	2.55	1.10
(M 3,5)	3,7	11	0,8	3.85	2.55	1.30
M 4	4,3	12	1	3.85	2.55	1.20
M 5	5,3	15	1,2	4.25	2.80	1.95
M 6	6,4	18	1,6	4.65	3.25	2.40
(M 7)	7,4	22	2	9.70	7.70	5.40
M 8	8,4	24	2	9.70	7.70	5.80
M 10	10,5	30	2,5	14.10	11.30	8.90
M 12	13	37	3	27.—	21.60	16.60
(M 14)	15	44	3	40.20	32.20	24.90
M 16	17	50	3	40.20	32.20	25.10
(M 18)	20	56	4	81.—	65.—	50.70
M 20	22	60	4	85.50	68.50	55.—
				100		
				50		


Unterlagsscheiben ohne Fase

Rondelles sans chanfrein

aus Stahl gestanz, 100-140 HV
verzinkt-gelb

en acier étampé, 100-140 HV
zingué-jaune



für Schrauben pour vis	d 1	d 2	s	100	500	1000
M 3	3,2	9	0,8	3.85	2.55	1.15
M 4	4,3	12	1,0	3.85	2.55	1.25
M 5	5,3	15	1,2	4.25	2.80	1.95
M 6	6,4	18	1,6	4.65	3.35	2.50
M 8	8,4	24	2	10.30	8.30	6.30
M 10	10,5	30	2,5	18.—	14.20	11.70
M 12	13	37	3	33.—	26.20	22.50
M 16	17	50	3	47.40	37.90	31.80
				100		

* Härteklasse: 140 HV bis M 16 / 100 HV > M16 / * classe de duseté: 140 HV jusqu'a M 16 / 100 HV > M 16