

Spannhülsen leicht


aus Federstahl vergütet,
HV 422-560
schwarz


Goupilles élastiques légère

en acier ressort traité,
HV 422-560
noir

~ISO 13337

~ISO 13337



Nenn- ϕ / ϕ nominal	2	3	4	5	6	8	10	12
s	0,2	0,3	0,5	0,5	0,75	0,75	1	1
a	0,2	0,25	0,5	0,5	0,7	1,5	2	2
d 1 min. Δ)	2,3	3,3	4,4	5,4	6,4	8,5	10,5	12,5
d 2~	1,9	2,7	3,4	4,4	4,9	7	8,5	10,5
L	100	100	100	100	100	100	100	100
4	9.90							
5	9.90							
6	9.90							
8	10.10							
10	10.10	11.60	13.—	13.—				
12	10.10	11.70	11.95	13.—				
14			13.20	13.30				
16		12.40	13.30	14.70	17.—			
18		12.60		15.50				
20	10.60	13.—	13.50	15.50	17.70	28.—	34.40	
24		13.30	13.80	17.—	21.—		39.90	
26			14.—		21.—	32.30	40.50	
30			14.40	19.55	22.90			
32					25.80	34.40	48.80	
36			16.—	21.—	28.—		51.60	
40			17.75	19.40	29.50	37.80	58.50	162.—
45			18.50	22.20		38.40	63.50	
50			18.80	23.20		45.40	67.70	173.—
55							78.—	
60								193.—
	100	100	50	50	50	50	50	50

 Δ) Masse vor dem Einbau / Dimensions avant montage