


Zylinderstifte

Ausführung B - Toleranz h8 mit Kegelschuppe

aus Automatenstahl gedreht
9 S Mn 28 K, nicht gehärtet
blank**Goupilles cylindriques**

exécution B - tolérance h8 à bout chanfreiné

en acier de décolletage décollé
9 S Mn 28 K, non trempé
clair

~DIN 7

~DIN 7

d -h8	1	1,5	2		2,5		3		4		5	
c~	0,2	0,3	0,35		0,4		0,5		0,63		0,8	
L	100	100	100	1000	100	1000	100	1000	100	1000	100	1000
3	7.20	7.90	8.40	3.—								
4	7.80	8.70	8.40	2.85			4.65	3.15				
5	7.80	8.70	8.40	2.90	8.90	3.20	5.10	3.60				
6	8.10	8.90	8.70	3.20	9.—	3.20	5.35	3.75	7.50	3.85	7.50	5.—
8	8.40	9.20	9.70	3.55	9.20	3.30	5.50	3.85	7.50	4.20	7.60	5.25
10	8.70	9.20	9.70	3.45	9.70	3.65	5.50	3.85	7.50	5.—	8.60	5.80
12	9.70	9.70	10.—	3.60	10.30	3.85	6.10	4.05	7.50	5.25	8.30	5.90
14			10.80	3.95	11.40	4.15	7.20	4.95	8.30	5.60	8.80	6.30
16		10.80	12.—	4.35	11.80	4.50	7.60	5.25	7.90	5.60	9.70	6.90
18									9.20	6.60		
20		13.20	13.20	4.95	15.—	6.—	8.10	5.80	9.20	6.60	11.10	7.90
24							9.70	7.—	10.90	7.70	12.80	9.10
25			15.70	5.60	16.80	6.50	9.70	7.—	10.90	7.70	12.80	9.10
26			16.40	6.20					12.—	8.50		
28							10.60	7.40	12.—	8.50		
30			16.80	6.20			10.60	7.40	12.—	8.50	14.60	10.40
32											14.80	10.60
36									14.80	10.60	14.80	10.60
40							13.—	9.20	14.80	10.60	14.80	10.60
45											19.80	14.—
50									17.90	12.60	22.10	15.80
60									21.50	15.30	25.80	18.—
70											28.80	22.50
80											32.—	24.80
100											47.60	37.—
		100	100	100	100		100		100		100	