


Zylinderstifte

Ausführung B - Toleranz h8 mit Kegelspitze

aus Automatenstahl gedreht
9 S Mn 28 K, nicht gehärtet
blank**Goupilles cylindriques**

exécution B - tolérance h8 à bout chanfreiné

en acier de décolletage décollé
9 S Mn 28 K, non trempé
clair

~DIN 7

~DIN 7

d -h8	6		8		10		12		16	
c~	1,2		1,6		2		2,5		3	
L	100	1000	100	1000	100	1000	100	1000	100	1000
6	8.10	5.70								
8	8.60	6.10								
10	8.60	6.60								
12	10.60	7.40								
14	11.10	7.90								
16	12.40	8.80	18.10	12.80	24.50	19.10				
20	13.50	9.70	20.40	14.40	27.50	21.40	39.50			
24	16.10	11.30	25.20	17.70			53.40			
25	16.10	11.30	25.20	17.70	32.70	25.20				
26							53.40			
28	17.60	12.50					53.40			
30	17.60	12.50	25.10	19.60	39.50	30.80	53.40			
35	19.50	13.90					61.—			
36	22.—	15.70	30.50	23.80	49.70	38.60				
40	22.—	15.70	30.50	23.80	49.70	38.60	68.50	150.—		
45	23.10	18.10	39.50	30.60	59.—	45.60	78.50			
50	25.20	19.70	40.10	30.90	61.—	47.30	85.50			
55	28.80	22.50	45.90	36.10	70.—	53.70	94.—	207.—		
60	31.30	24.10	48.20	37.30	71.50	55.50	87.50	219.—		
70	37.—	29.10	59.—	45.60	85.50	66.50	104.—			
80	43.—	33.70	68.50	53.10	90.—	74.50		288.—		
90			79.50	61.—						
100			92.—	71.50	119.—	97.—	152.—			
120					143.—	118.—	177.—			
		100	100		100		50		25	