

Scheibensfedern

(Woodruff)


Clavettes disque

(Woodruff)


aus Stahl C 45 K

blank

en acier C 45 K

clair

~ISO 3912

b -h9 Breite b -h9 largeur	h -h12 Höhe h -h12 hauteur	L~	D	Wellen- ϕ + ϕ d'axe +	Wellen- ϕ < ϕ d'axe <	100
2	2,6	6,76	7	6	8	24.50
2	3,7	9,66	10	6	8	17.70
(2)	(5)	12,65	13	6	8	30.30
(2,5)	(3,7)	9,66	10	8	10	19.90
3	3,7	9,66	10	8	10	20.—
3	5	12,65	13	8	10	20.60
3	6,5	15,72	16	8	10	20.80
4	5	12,65	13	10	12	21.30
4	6,5	15,75	16	10	12	21.40
4	7,5	18,57	19	10	12	30.40
5	6,5	15,72	16	12	17	21.70
5	7,5	18,57	19	12	17	34.50
5	9	21,63	22	12	17	43.40
(5)	(10)	24,49	25	12	17	69.—
6	9	21,63	22	17	22	46.60
(6)	(10)	24,49	25	17	22	60.50
6	11	27,35	28	17	22	78.—
8	11	27,35	28	22	30	78.—
8	13	31,43	32	22	30	98.50
10	11	27,35	28	30	38	107.—
10	13	31,43	32	30	38	121.—
10	16	43,08	45	30	38	213.—
						100