



Hammerschrauben Typ U


Fausses-vis à métaux type U

aus Stahl, einsatzgehärtet
vernickelt

en acier, cémenté-trempé
nickelé



d 1	1,47	1,85	2,49	2,89	3,5	3,86
Loch- \emptyset / \emptyset -du trou	1,3	1,7	2,18	2,64	3,05	3,45
d 2	1,16-1,24	1,52-1,6	2,02-2,1	2,33-2,43	2,84-2,94	3,09-3,2
d 3 max.	2,5	3,2	4,1	5,4	6,6	7,3
k max.	0,86	1,24	1,75	2,18	2,67	2,81
s	1,19	1,19	1,19	1,45	1,45	1,45
L mm	100	100	100	100	100	100
3,17	4.85	4.85	4.85			
4,76	4.85	6.—	6.—	6.—		
6,35	4.85	6.—	6.—	7.20	7.20	
7,93			6.60	7.30	7.80	7.80
9,52				7.80	7.80	
	100	100	100	100	100	100

d 1	4,16	5,31
Loch- \emptyset / \emptyset -du trou	3,65	4,85
d 2	3,35-3,45	4,39-4,49
d 3 max.	7,9	10,4
k max.	3,04	3,88
s	1,85	1,85
L mm	100	100
9,52	10.—	
12,70		16.80
15,87	11.40	
	100	100